



IT IS LIGHTING IT IS DIFFERENT



LED CATALOG 2017



ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City,Guangdong Province,China

Tel: (+86)757-86488332

Fax: (+86)757-81261265

E-mail: jbu@zlamp.com.cn

sales@zlamp.com.cn

Website: www.zlamp.com.cn

<http://zlamp.gmc.globalmarket.com>



LED FILAMENT BULB



- Retrofit dimension of the traditional incandescent filament bulbs
- Warm light at 2500~2700K
- Upto 90% energy saving
- Compliance with ERP

ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City, Guangdong Province, China
Tel: (+86)757-86488332 Fax: (+86)757-81261265
E-mail: jbu@zlamp.com.cn sales@zlamp.com.cn
Website: www.zlamp.com.cn
http://zlamp.gmc.globalmarket.com



FILAMENT CANDLE



M MODEL	ZL-FIL-CANW2	ZL-FIL-CANW4
V INPUT VOLTAGE	AC 220~240V	
W MAX. WATTAGE	2W	4W
Pcs QUANT. OF LEDS	2pcs	4pcs
lm LUMEN OUTPUT	200lm	400lm
Tc COLOR TEMP.	2700K	
D DIMENSION	D:35MM, H:98MM	

FILAMENT TURN-TIP CANDLE



M MODEL	ZL-FIL-CANW2	ZL-FIL-TCANW4
V INPUT VOLTAGE	AC 220~240V	
W MAX. WATTAGE	2W	4W
Pcs QUANT. OF LEDS	2pcs	4pcs
lm LUMEN OUTPUT	200lm	400lm
Tc COLOR TEMP.	2700K	
D DIMENSION	D:35MM, H:125MM	

FILAMENT GLOBE



M MODEL	ZL-FIL-GLOW2	ZL-FIL-GLOW2
V INPUT VOLTAGE	AC 220~240V	
W MAX. WATTAGE	2W	4W
Pcs QUANT. OF LEDS	2pcs	4pcs
lm LUMEN OUTPUT	200lm	400lm
Tc COLOR TEMP.	2700K	
D DIMENSION	D:45MM, H:80MM	

Filament A60



M MODEL	ZL-FIL-A60W4	ZL-FIL-A60W6	ZL-FIL-A60W8
V INPUT VOLTAGE	AC 220~240V		
W MAX. WATTAGE	4W	6W	8W
Pcs QUANT. OF LEDS	4pcs	4pcs	6pcs
lm LUMEN OUTPUT	400lm	600lm	800lm
Tc COLOR TEMP.	2700K		
D DIMENSION	D:60MM, H:108MM		

Filament G80 Candle



M MODEL	ZL-FIL-G80W4	ZL-FIL-G80W6	ZL-FIL-G80W8
V INPUT VOLTAGE	AC 220~240V		
W MAX. WATTAGE	4W	6W	8W
Pcs QUANT. OF LEDS	4pcs	4pcs	6pcs
lm LUMEN OUTPUT	400lm	600lm	800lm
Tc COLOR TEMP.	2700K		
D DIMENSION	D:80MM, H:120MM		

Filament G95 Candle



M MODEL	ZL-FIL-G95W4	ZL-FIL-G95W6	ZL-FIL-G95W8
V INPUT VOLTAGE	AC 220~240V		
W MAX. WATTAGE	4W	6W	8W
Pcs QUANT. OF LEDS	4pcs	4pcs	6pcs
lm LUMEN OUTPUT	400lm	600lm	800lm
Tc COLOR TEMP.	2700K		
D DIMENSION	D:95MM, H:135MM		

Filament G125 Candle



M MODEL	ZL-FIL-G125W4	ZL-FIL-G125W6	ZL-FIL-G125W8
V INPUT VOLTAGE	220~240V		
W MAX. WATTAGE	4W	6W	8W
Pcs QUANT. OF LEDS	4pcs	4pcs	6pcs
lm LUMEN OUTPUT	400lm	600lm	800lm
Tc COLOR TEMP.	2700K		
D DIMENSION	D:125mm H:170mm		

Filament ST64 Candle



M MODEL	ZL-FIL-ST64W4	ZL-FIL-ST64W6	ZL-FIL-ST64W8
V INPUT VOLTAGE	220~240V		
W MAX. WATTAGE	4W	6W	8W
Pcs QUANT. OF LEDS	4pcs	4pcs	6pcs
lm LUMEN OUTPUT	400lm	600lm	800lm
Tc COLOR TEMP.	2700K		
D DIMENSION	D:64mm H:142mm		

LED Module for Ceiling lamp



- Replaceable LED module for ceiling lamp:
- Flexible, cost efficient:
- Anti-Glare with wide beam angle:
- 3 steps CCT or Brightness change by switch functions available:

ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City,Guangdong Province,China
Tel: (+86)757-86488332 Fax: (+86)757-81261265
E-mail: jbu@zlamp.com.cn sales@zlamp.com.cn
Website: www.zlamp.com.cn
http://zlamp.gmc.globalmarket.com



LED Module for Ceiling lamp

M MODEL	ZL-CMW15	ZL-CMW15-S-D	ZL-CMW15-CCT-S-D
V INPUT VOLTAGE	220-240V	220-240V	220-240V
W MAX. WATTAGE	15W	15W	16W
lm LUMEN OUTPUT	1200lm	1150lm	1100lm
LED LED TYPE	SMD 2835	SMD 2835	SMD 2835
Tc COLOR TEMP.	3000K/4000K/6000K	3000K/4000K/6000K	3000K-4000K-6000K
D DIMENSION	L:84mm W:84mm H:15mm		
REMARK	100% ↓ 1 x ON 50% ↓ 2 x OFF/ON 10% ↓ 3 x OFF/ON 2700K ↓ warm white 1 x ON 6500K ↓ daylight 2 x OFF/ON 4000K ↓ neutral white 3 x OFF/ON		

LED G4 G9



- Retrofit size for direct replacement of the halogen bulb
- Cost efficient
- Compliance with ErP

ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City, Guangdong Province, China
Tel: (+86)757-86488332 Fax: (+86)757-81261265
E-mail: jbu@zlamp.com.cn sales@zlamp.com.cn
Website: www.zlamp.com.cn
http://zlamp.gmc-globalmarket.com



LED Ceramic G9



M MODEL	ZL-G9W3.5-C
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	3.5W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	320lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:16MM, H:50MM



LED Ceramic G9 no flicker



M MODEL	ZL-G9W3.5-C
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	3.5W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	320 lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:16MM, H:50MM



LED Ceramic G9 no flicker



M MODEL	ZL-G9W4-C
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	4W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	420lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:19MM, H:55MM



LED Ceramic G9 Dimmable



M MODEL	ZL-G9W3-C-D
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	3W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	300lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:16MM, H:50MM



LED Ceramic G9 STEP Dim



M MODEL	ZL-G9W3-C-S-D
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	3W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	300lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:16MM, H:50MM



LED Silicon G4



M MODEL	ZL-G4W2-S
V INPUT VOLTAGE	AC/DC 12V
W MAX. WATTAGE	2W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	220lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:10MM, H:39MM



LED PC G4



M MODEL	ZL-G4W1.5-PC
V INPUT VOLTAGE	AC/DC 12V
W MAX. WATTAGE	1.5W
LED LED TYPE	SMD2835
lm LUMEN OUTPUT	110lm
Δ BEAM ANGLE	330°
Tc COLOR TEMP.	3000K/4000K/6000K
id DIMENSION	D:12MM, H:37MM

SMD LED



- Milky glass housing provide soft lighting output
- Wide beam angle upto 330°
- Cost efficient
- Widely used in restaurant, hotel, homeetc
- Dimmable version available

ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City,Guangdong Province,China
Tel: (+86)757-86488332 Fax: (+86)757-81261265
E-mail: jbu@zlamp.com.cn sales@zlamp.com.cn
Website: www.zlamp.com.cn
http://zlamp.gmc-globalmarket.com



ERP

SMD LED T30

	M MODEL	ZL-T30W4-GU10	ZL-T30W4-E14
	V INPUT VOLTAGE	AC 220-240V	
	W MAX. WATTAGE	4W	
	LED LED TYPE	SMD 2835	
	lm LUMEN OUTPUT	350 lm	
	BASE	GU10	E14
	Tc COLOR TEMP.	3000K/4000K/6000K	
	ID DIMENSION	D:30mm H:90mm	D:30mm H:95mm

ERP

SMD LED M2U

	M MODEL	ZL-M2UW5-GU10	ZL-M2UW5-E14
	V INPUT VOLTAGE	AC 220-240V	
	W MAX. WATTAGE	5W	
	LED LED TYPE	SMD 3014	
	lm LUMEN OUTPUT	430 lm	
	BASE	GU10	E14
	Tc COLOR TEMP.	3000K/4000K/6000K	
	ID DIMENSION	D:30mm H:125mm	D:30mm H:130mm



PLASTIC-ALUMINUM G80/G95/G120

	M MODEL	ZL-PA-G80W10	ZL-PA-G95W12	ZL-PA-G120W15
	V INPUT VOLTAGE	180-250VAC		
	W MAX. WATTAGE	10W	12W	15W
	LED LED TYPE	SMD 2835		
	lm LUMEN OUTPUT	950lm	1200lm	1500lm
	BEAM ANGLE	220°		
	Tc COLOR TEMP.	3000K/4000K/6000K		
	ID DIMENSION	D:80mm H:118mm	D:95mm H:139mm	D:120mm H:158mm

High Power LED Bulb

	M MODEL	ZL-T70W15	ZL-T80W20	ZL-T100W30	ZL-T120W40	ZL-T135W50
	V INPUT VOLTAGE	185-250V				
	W MAX. WATTAGE	15W	20W	30W	40W	50W
	LED LED TYPE	SMD2835				
	lm LUMEN OUTPUT	110-1200lm	1600-1700lm	2500-2600lm	3000-3100lm	3600-3700lm
	PF POWER FACTOR	>0.5	>0.5	>0.9	>0.9	>0.9
	BASE	E27			E27/E40	
	ID DIMENSION	D:70mm H:125mm	D:80mm H:145mm	D:100mm H:185mm	D:120mm H:225mm	D:135mm H:265mm

LED SPOTLIGHT



- Glass/Plastic + Aluminum housing
- High lumen output, retrofit GU10 for 75W halogen lamp
- Cost Efficient
- With 6000 hours ErP test report

ZLAMP(FOSHAN)ENTERPRISE CO., LTD.

Add: No.68 Fenjiang North Rd, Chancheng Area, Foshan City, Guangdong Province, China
Tel: (+86)757-86488332 Fax: (+86)757-81261265
E-mail: jbu@zlamp.com.cn sales@zlamp.com.cn
Website: www.zlamp.com.cn
http://zlamp.gmc-globalmarket.com



ERP

SMD GLASS GU10



M MODEL	ZL-SMD-GUW3-G1
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	3W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	300lm
Δ BEAM ANGLE	110°
Tc COLOR TEMP.	3000K/4000K/6000K
D DIMENSION	D:50MM, H:56MM



ERP

SMD GLASS GU10



M MODEL	ZL-SMD-GUW5-G
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	5W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	450lm
Δ BEAM ANGLE	110°
Tc COLOR TEMP.	3000K/4000K/6000K
D DIMENSION	D:50MM, H:56MM



ERP

GLASS GU10



M MODEL	ZL-COB-GUW5-G	ZL-SMD-GUW5-G
V INPUT VOLTAGE	AC 180-250V	
W MAX. WATTAGE	5W	
LED LED TYPE	COB	SMD2835
lm LUMEN OUTPUT	450 lm	400 lm
Δ BEAM ANGLE	25°/40°/60°	
Tc COLOR TEMP.	3000K/4000K/6000K	
D DIMENSION	D:50MM, H:56MM	



NEW

DIM TO WARM GU10



M MODEL	ZL-SMD-GUW5-G-D2W
V INPUT VOLTAGE	AC 220-240V
W MAX. WATTAGE	5W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	400lm
Δ BEAM ANGLE	40°/60°
Tc COLOR TEMP.	2000K-2500K-3000K
D DIMENSION	D:50MM, H:56MM

PLASTIC-ALUMINUM GU10



M MODEL	ZL-SMD-PA-GUW5-SP	ZL-COB-PA-GUW6-SP
V INPUT VOLTAGE	AC 180-250V	
W MAX. WATTAGE	5W	6W
LED LED TYPE	SMD2835	COB
lm LUMEN OUTPUT	400 lm	500 lm
Δ BEAM ANGLE	40°	
Tc COLOR TEMP.	3000K/4000K/6000K	
D DIMENSION	D:50mm H:55mm	

ERP

PLASTIC-ALUMINUM GU10



M MODEL	ZL-PX-COB-GUW5	ZL-PX-COB-GUW7
V INPUT VOLTAGE	AC 180-250V	
W MAX. WATTAGE	5W	7W
LED LED TYPE	COB	
lm LUMEN OUTPUT	400 lm	530 lm
Δ BEAM ANGLE	40°	
Tc COLOR TEMP.	3000K/4000K/6000K	
D DIMENSION	D:50MM, H:56MM	

SMD GLASS MR16



M MODEL	ZL-SMD-MRW5-G
V INPUT VOLTAGE	AC/DC 12V
W MAX. WATTAGE	5W
LED LED TYPE	SMD 2835
lm LUMEN OUTPUT	400lm
Δ BEAM ANGLE	40°
Tc COLOR TEMP.	3000K/4000K/6000K
D DIMENSION	D:50MM, H:50MM

COB GLASS MR16



M MODEL	ZL-COB-MRW5-G
V INPUT VOLTAGE	AC/DC 12V
W MAX. WATTAGE	5W
LED LED TYPE	COB
lm LUMEN OUTPUT	420lm
Δ BEAM ANGLE	40°
Tc COLOR TEMP.	3000K/4000K/6000K
D DIMENSION	D:50MM, H:50MM